

## ELECTRIC GRIDDLE SMOOTH COMPOUND PLATE



Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Cooking plate in compound (AISI 316L stainless steel+FE). EVEN-PRO SYSTEM. Delivered with: plate plug. Heating by heating elements made in AISI 309 stainless steel, safety thermostat. Working temperature (min-max): 70-260°C.



<i>Plate</i>	Compound - smooth	<i>Power supply</i>	Electricity
<i>Product fitting up</i>	Counter Top	<i>Worktop thickness</i>	2 mm

### Functional features

- Smooth cooking plate made in compound thickness 12 mm (9 mm special FE510D stainless steel + 3 mm AISI 316L stainless steel)
- Plate with satin-finish, recessed into the worktop; welded around the perimeter and sealed.
- Operating temperature: 70-260°C.
- Dimensions of the cooking plate (W x D): 330 x 530 mm. Frontal simmering zone 50 mm.
- n. 1 cooking area power rated at 5.5 kW.
- EVEN-PRO Ensures high cooking uniformity and temperature stability. The cooking heating elements are integrated with a 5 mm aluminum diffuser ensuring quick temperature rise, high efficiency in the heat transfer, temperature stability and energy efficiency.
- EASY-WASH: this is the program to clean the cooking plate bringing the surface temperature up to 75°C, in order to wash it reducing water and detergent.
- Commutable to 230V3 50/60 Hz
- Group of 3 armoured heating elements made of in AISI 309 stainless steel.

### Constructional features

- Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Fett drain outlet diameter 32 mm with removable heat-resistant food-grade plastic plug.
- Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1 lt.
- Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- Access to all components through front compartment or control console.

### Safety equipment and approvals

- Safety thermostat protecting the appliance and electric parts.
- Max temperature safety thermostat.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- IPX4 protection rating.

### Optional

- Splash guards, cleaning plate scraper and blades; pipe for the water discharge during the cleaning of the plate.

### Technical Data

<i>Working voltage</i>	400V 3N~ / 230V 3~ / 50÷60 Hz	<i>Electric Power</i>	5,1 kW
<i>Dimensions</i>	40x72x25 cm	<i>Packing</i>	46x82x65 cm

