

FD15TPV



Refrigerator glass door-GN2/1-AISI304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 2 glass doors. Temperature ranges: 0/+10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI
Series	Freezy Prime
Supplier's model identifier	FD15TPV
Category	display cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	E
Energy consumption, kWh/24h	4,5
Energy consumption/year, kWh/a	1643
Method for energy consumption	EN 22041
Energy Efficiency Index	76,74
Net usable volume, lt	932
Volume, gross, lt	1180
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,115
LWA dB(A)	51
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	601

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

ANGELO PO GRANDI CUCINE S.p.a. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 09/01/2024 09.36.32



FD15TPV



Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,32

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel (inner ceiling made of special anti-fingerprint steel)
Insulation thickness, mm	75
Door	2 glass doors
Standard hinging door	with self-closing device for openings inferior to 90°
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	yes
Lighting	LED lighting
Couple of guides (n.)	6 pair of AISI 304 stainless steel runners
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	48

Dimensions and weights

Packing (LxDxH), cm	154x85,5x207
Dimensions (LxDxH), cm	150x80x204
Gross Weight (kg)	224
Net Weight (kg)	204

Notes

Notes	Models ...PV, installation allowed to an altitude up to 800 metres above the sea level
-------	--

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

