

# FD7TPV



## Refrigerator glass door-GN2/1-AISI304-Freezy Prime

One-piece structure in AISI 304 stainless steel. Single compartment, GN2/1. 1 glass door. Temperature ranges: 0/+10°C. Control panel with digital thermometer- thermostat. Fan-assisted refrigeration with external evaporator. Automatic defrosting. Lighting and key-operated lock.



### General information

Supplier/producer 's name	SAGI
Series	Freezy Prime
Supplier's model identifier	FD7TPV
Category	display cabinet
Type	refrigerator
Line	catering - GN 2/1

### Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	E
Energy consumption, kWh/24h	3,1
Energy consumption/year, kWh/a	1131,5
Method for energy consumption	EN 22041
Energy Efficiency Index	82,3
Net usable volume, lt	466
Volume, gross, lt	590
Climate class	4 (+30°C, 55% R.H.)
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,08
LWA dB(A)	38
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	406

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

ANGELO PO GRANDI CUCINE S.p.a. con socio unico  
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy  
[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Angelo Po S.p.a. reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 08/01/2024 20.33.47



# FD7TPV



Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,22

## Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel (inner ceiling made of special anti-fingerprint steel)
Insulation thickness, mm	75
Door	1 glass door
Standard hinging door	on the right/no-reversible on the site with self-closing device for openings inferior to 90°
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	21/60
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

## Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

## Standard

Key-lock	yes
Lighting	LED lighting
Couple of guides (n.)	3 pair of AISI 304 stainless steel runners
Shelves (n.)	3, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	48

## Dimensions and weights

Packing (LxDxH), cm	79x85,5x213
Dimensions (LxDxH), cm	75x80x204
Gross Weight (kg)	142
Net Weight (kg)	127

## Notes

Notes	Models ...PV, installation allowed to an altitude up to 800 metres above the sea level
-------	--

Refrigerator glass door-GN2/1-AISI304-Freezy Prime

